

ZDAPMB1







1x ZDA4.6

1x SOT Cable

1x ZDAISOT



Installation Tools Required





Tools required:



V 1x Plastic Pry Tool

1. Remove the stereo panel



3. Take out the stereo ->



2. Unscrew the screws



3.5 Disconnect all the connectors



Tools required:



4. Remove the black and white connector



6. Connect the black and white connectors to the SOT cable.



5. Connectors removed



7. Connect the SOT cable to the OEM connector



Tools required:





8. Remove the center panel



10. Pull the panel towards you



9. Remove the lower center panel. On each side there is a plastic lid, remove both and unscrew the screws behind them.



11. Disconnect the connector (pull it upwards)



Tools required:

12. Remove the entire side panel



14. Remove the battery panel



13. The back of the panel



15. Remove the threshold panel



Tools required:



16. Connect the ZDAISOT to the SOT cable*



18. Pull up the carpet



17. Route the cable as in the picture



19. Route the ZDAISOT in the center



* OBS! Use the external 10ohm resistor cable on the speaker side.

Tools required:



20. Remove the passenger seat (pull straight up)



22. Route it under the carpet and up



21. Route the cable under the seat



23. Place the ZDA4.6 under the seat



Tools required:







25. Physical install is now complete



Go to phoenixgold-eu.com/downloads/ and download the ZDA4.6 software and your 26. Phoenix Gold sound curve



Software Installation 1

Tools required:



20. Press "Program"



21. Press "Load PC Presets File"



22. Go to your saved location and choose your Phoenix Gold sound curve, then click "Open"

ZDA4.6		
+12 +9 +6 +3 0dB -3 -6 -9		0.000
-12 20 30 40 50 70 100 20	Look in: Phoenix Gold 🔹 🗲 🖻 🕆 🔝 - 20K	0.000 0 0.000 Ms OCm O In
ID: 1 2 3 4 F: 31 65 125 25 Q: 2515 2515 2515 G: 00 00 00 00 EQ 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Name Date modified Date modified Phoenix Gold Sound Curve.rdas 24/12/2022 01:26 File name: Phoenix Gold Sound Curve Open Files of type: rdas Cancel	HPF LPF Type: Link_Ril ▼ Link_Ril ▼ Freq: 20Hz ÷ 20000Hz ÷ Oct: Oct: 12dB/Oct ▼ 12dB/Oct ▼
VOLUME 6 -10 -20 -20 -10 -20 -10 -20 -10 -20 -10 -20 -10 -20 -10 -10 -20 -10 -20 -10 -10 -20 -10 -20 -10 -10 -20 -10 -10 -20 -10 -10 -20 -10 -10 -10 -10 -10 -10 -10 -1	0 0.0dB 0 0.0dB 0	System Program Reset Output Link Output W PHOENIX GOLD ON Line Name : Phoenix Gold

Software Installation 2

Tools required:



1x Computer

23. Press "Program"





24. Press "Save As Machine Preset"





Software Installation 3

Tools required:



1x Computer

26. Press "OK". The sound curve is now installed and saved to the ZDA4.6.

ZDA4.6			
+12 +9 +6 +3 0dB -3 -6 -9 -12 20 30 40 50 70 100 200 No Preset X L 20K	43 77 0 0 0 0 0 0 0 0 0 0		
ID: 1 2 3 4 F: 31 65 125 250 Q: 2515 2515 2515 2515 G: 0.0 0.0 0.0 0.0 EQ I I I I Save Quit Save Quit	HPF LPF Type: Lpr Luk_Ri LkR Freq: 2000Hz Oct: Oct: 24dB/Oct 12dB/Oct		
VOLUME 0 0.0dB 0 0 0.0dB 0 0 0.0dB 0 0 0.0dB 0 <th>System & PHOENIXGOLD Program Reset Output Link Output Name:</th>	System & PHOENIXGOLD Program Reset Output Link Output Name:		



On Behalf of the Phoenix Gold team, Thank you for choosing us!

Your installation is complete and we hope that your new upgraded system will bring you joy and happiness for many years to come when listening to your favorite music. As always, our goal is bringing you The Gold Standard in Sound.



www.phoenixgold-eu.com